

Product data sheet

eNet radio hand-held transmitter 1-gang



Reference number

FM HS 1 T

eNet radio hand-held transmitter

1-gang Toggle

New system feature: Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0

Intended use

- Radio hand transmitter for radio transmission of switching, dimming, and blind movement commands
- Operation with radio actuators from the eNet system

Product characteristics

- One button for switching and dimming a channel
- Status indication with LED
- Battery-powered device
- Signalling of transmission errors can be switched off

Can be set with eNet server:

- Scenes: All On, All Off, individual scenes
- Operating locks

Supplementary functions with eNet server:

- Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0
- Update of the device software
- Reading of error memory

Technical data

| | |
|-----------------------------------|---------------------------------|
| Rated voltage: | DC 3 V |
| Battery type: | 1 x lithium CR 2450N (included) |
| Ambient temperature: | -5 ... +45 °C |
| Dimensions (L x W x H): | 55 x 40.5 x 15 mm |
| Radio frequency: | 868.0 ... 868.6 MHz |
| Transmitting power: | max. 20 mW |
| Transmission range in free field: | typical 100 m |
| Receiver category: | 2 |



Colour:
anthracite