

Product data sheet

eNet radio hand-held transmitter 4-gang



Reference number

FM HS 4

eNet radio hand-held transmitter

4-gang

New system feature: Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0

Intended use

- Hand transmitter for radio transmission of switching, dimming, blind movement and scene commands
- Operation with radio actuators from the eNet system

Product characteristics

- Two adjacent buttons each belong to one channel
- Status indication with LED
- Switch-on brightness of dimmer actuators can be saved
- Battery-powered device
- Scenes, radio hand transmitter, 4x: All Off, seven individual scenes
- Signalling of transmission errors can be switched off

Can be set with eNet server:

- Scene All On
- Operating locks

Supplementary functions with eNet server:

- Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0
- Update of the device software
- Reading of error memory

Technical data

Rated voltage:	DC 3 V
Battery type:	1 x lithium CR 2450N (included)
Ambient temperature:	-5 ... +45 °C
Dimensions (L x W x H):	93 x 53 x 15.5 mm
Radio frequency:	868.0 ... 868.6 MHz
Transmitting power:	max. 20 mW
Transmission range in free field:	typical 100 m
Receiver category:	2



Colour:
anthracite