

Product data sheet

Sonos gateway



Reference number

MR-SONOS-REG

KNX Sonos gateway

Rail mounting device, 2 rail units
ETS product family: Multimedia
Product type: Multiroom

Intended use

- Controlling of Sonos audio devices via KNX
- Mounting on DIN rail according to EN 60715 in distribution boxes

Product characteristics

- Control of up to 30 Sonos devices via KNX devices, independent of the Sonos App
- Dynamic group creation of up to 10 zones with one master and five slave devices each via KNX objects
- Party mode: same music for all rooms
- Volume control for master, slaves and the whole group
- Control of play lists
- Playing music from microSD card (not included) in the Sonos gateway
- Title, artist and album on KNX text objects
- Integrated data network switch with two RJ45 terminals
- Requires ETS version 4.2 or 5.0.2 or higher

Technical data

KNX medium:	TP 64
External supply	
Rated voltage:	DC 24 ... 30 V \pm 10 %
Connection:	connecting terminal yellow/white
Power consumption:	typical 2 W (at DC 24 V, two Ethernet cables connected)
IP communication:	Ethernet 10/100 BaseT (10/100 Mbit/s)
IP connection:	2 x RJ45
Protocols:	ARP, ICMP, IGMP, UDP/IP, DHCP, AutoIP, KNXnet/IP (Core, Device Management)
Memory card:	max. 32 GB microSDHC
Ambient temperature:	0 ... +45 °C
Storage/transport temperature:	-25 ... +70 °C
Mounting width:	36 mm (2 rail unit)
Rated voltage KNX:	DC 21 ... 32 V SELV
Connection, KNX:	terminal