





Intelligent Control at an Entry Price Point.

The ELAN SC-100 System Controller offers robust performance at a price point that creates new opportunities for revenue and profit.

- Perfect for single room media control
- Competitive price point bundled with the ELAN HR10 remote
- Faster installations
- Priced as the "standard" for the builder channel, enabling easy add-on packages with Z-Wave solutions

Where a universal remote would only provide access to media, lighting or climate, the EL-SC-100 enables intelligent integration of additional home systems that provide real value. For smaller to moderate installations the EL-SC-100 provides a single point of control and automation for media, climate, lighting, security, surveillance and more. With all control through the award-winning ELAN user interface, the EL-SC-100 delivers an exceptional experience.



EL-SC-100 System Controller

ORDER NO. EL-SC-100 INTERNATIONA

FEATURES

- Compatible works with all current ELAN user interfaces, including remotes, touch panels and keypads, as well as iOS and Android mobile devices and PC and Mac computers.
- Reliable Ultra-efficient fan-less design with no moving parts delivers longlasting reliability operation.
- Flexible The compact design allows installation in cabinets, structured wiring cabinets or behind a display.
- Powerful Easily automates small to moderate sized installations.
- A great partner Extender mode enables use with gSC series controllers on larger installations.
- PoE or Wi-Fi connection allows for placement flexibility.

CONNECTIONS	
RS-232	(1) RJ-45 Connector
ELAN Sense	(1) 3.5mm Connector
IR Output	(3) 3.5mm Connectors (Mono), - 12V DC
Audio	(1) 3.5mm Connectors (Stereo)
On-Screen Display	(1) HDMI Female Connector
USB	(1) USB A Connector
Ethernet	(1) RJ-45 PoE Connector
Wi-Fi	802.11 b/g/n
Power	Coaxial Type A, 2.5mm inside diam.

SYSTEM	
Software compatibility	Requires Core Module 8.4 or above
Updates	Managed by Core Module software

GENERAL	
Power	Included Power Supply, 120/240VAC input 12VDC 1A output
Temperature	32 °F to 131 Degrees° F
Operating Humidity	90% Maximum (Non-Condensing)
Mounting	Free standing, Wall mount, Structured wiring cabinet
Product Dimensions	(in.) 6 15/16 W x 1 1/4 H x 5 D (mm) 176 W x x 31 H x 126 D
Product Weight	0.8 lb / 0.36 Kg
Certifications	CE, FCC, C-Tick





www.elanhomesystems.com