

Product data sheet

Room controller display compact module



Reference number

4093 KRM TS D

Room controller display compact module

can be extended by means of a push-button extension module, ref.-no.: 409.. TSEM
Adapter frames are included in delivery: ref.-no. LS 4 AR for LS range (pre-mounted) and
ref.-no. CD 4 AR for CD range.
AS / A ranges without adapter frame.

Recommended mounting height: 1.5 m

Intended use

- Measurement and feedback control of the room temperature
- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush box according to DIN 49073

Product characteristics

All buttons can be assigned with push-button sensor functions or functions for controller operation.

- KNX medium: TP 256
- Four red status LEDs
- One blue operation LED as an orientation light and to indicate the programming status
- Integrated bus coupling unit
- Connection for a push-button extension module, 1-4 gang
- Integrated temperature sensor
- Room temperature control with setpoint value specification
- Display of room or set temperature
- Display of outdoor temperature – with external sensor, e.g. weather station
- Display of time, in conjunction with KNX time encoder
- Push-button functions switching, dimming, blind control, value transmitter, scene recall, etc.
- Push-button function or rocker function, vertical or horizontal
- Fan coil application with up to 8 fan speeds and auto function
- Transparent cover kit (included) for temporary site use without design covers