

# Product data sheet

## Push-button extension module



### Reference number

LS 5094 TSEM

### Push-button extension module

including transparent cover ref.-no.: LS 50 NA  
for the extension of the Universal push-button module (ref.-no.: LS 509.. TSM) and room temperature controller module (ref.-no.: LS 5178 TSM) with up to 4 additional push-buttons

### Intended use

- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush box according to DIN 49073

### Product characteristics

- One or two functions per button
- To be completed with cover kit
- Inscription field can be illuminated
- One status LED per button, red, green or blue, adjustable
- One operation LED as orientation light and programming status – red, green or blue, adjustable
- Brightness of status LED, operation LED and inscription field adjustable, can be changed during operation, e.g. during night times
- Measurement of room temperature
- Extension unit for room temperature controller
- Disabling function: Disabling or change function mode of single or all button functions
- Alarm function, optional acknowledge by pressing any button
- Energy saving mode
- Transparent cover kit (included) for temporary site use without design covers
- Cable length: max. 30 m, cable type: J-Y(St)Y 2 x 2 x 0.8 mm

### Spare part:

transparent cover ref.-no.: LS 50 NA

### Accessories:

Neutral cover ref.-no.: LS 50 NA W, LS 50 NA WW, LS 50 NA LG, LS 50 NA SW, AL 50 NA-L, ES 50 NA-L, AL 50 NA AN-L, ME 50 NA C-L, ME 50 NA AT-L, ME 50 NA D-L

### Version:

4-gang