

# Product data sheet

## eNet radio transmitter module 2-gang



### Reference number

FM A 5002 M

### eNet radio transmitter module 2-gang

including transparent cover ref.-no.: A 50 NA

including mounting plate, adhesive pad and fastening screw

for cover kit 2-gang, ref.-no.: A 502 TSA ..

New system feature: Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0

### Intended use

- Radio sensor for transmission of switching, dimming, blind movement and scene commands
- Operation with radio actuators from the eNet system
- Mounting on appliance box according to DIN 49073, screw fixing on walls or adhesive fixing on smooth, even surfaces (glass).

### Product characteristics

- Two adjacent buttons each belong to one channel
- Display of the actuator status for status poll by a green LED per channel
- Display of the transmission status by a red LED
- Switch-on brightness of dimmer actuators can be saved
- Battery-powered device (battery compartment accessible from front)
- Signalling of transmission errors can be switched off

### Can be set with eNet server:

- Scene All On
- Operating locks

### Supplementary functions with eNet server:

- Fully-encrypted radio transmission (AES-CCM) from eNet Server software version 2.0
- Update of the device software

### Spare part:

Transparent cover ref.-no.: A 50 NA

### Accessories:

Neutral cover ref.-no.: A 50 NA W, A 50 NA WW, A 50 NA SW, A 50 NA AL, A 50 NA CH, A 50 NA MO

### Technical data

Rated voltage:	DC 3 V
Battery type:	1 x lithium CR 2450N (included)
Ambient temperature:	-5 ... +45 °C
Radio frequency:	868.0 ... 868.6 MHz
Transmitting power:	max. 20 mW
Transmission range in free field:	typical 100 m

Receiver category: 2

