

With setting "LED trailing edge phase control" the max. connection power for HV LED lamps and electronic transformers with LV LED doubles.

| | |
|--|---|
| Ohmic-capacitive: | 20 ... 210 W |
| Capacitive-inductive: | not permitted |
| Ohmic-inductive: | 20 ... 210 VA |
| Ohmic and HV LED: | typical 3 ... 50 W |
| Ohmic and CFL: | typical 3 ... 50 W |
| Amplifiers: | see instructions for amplifier |
| Connection: | screw terminals |
| single wire: | 1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ² |
| stranded without ferrule: | 1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ² |
| stranded with ferrule: | 1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 1.5 mm ² |
| Number of satellite units | |
| Satellite insert 2-wire 1720 NE: | unlimited |
| Satellite insert 3-wire 1723 NE: | 10 |
| Rotary satellite insert 3-wire 1733 DNE: | 10 |
| Push-buttons: | unlimited |
| Total length of extension unit cable: | max. 100 m |
| Total length power cable: | max. 100 m |

