

Product data sheet

Universal push-button module 3-gang



Reference number

LS 52931 ST

KNX universal push-button module 3-gang

including transparent cover ref.-no.: LS 50 NA

for cover kit 3-gang, ref.-no.: ..503 TSA .. in the LS range

can be extended by means of a push-button extension module, ref.-no.: LS 509.. TSEM

ETS product family: Push-button Product type: 3-gang push-button available September 2023

Intended use

- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush box with dimensions according to DIN 49073

Product characteristics

- KNX medium: TP 256
- Push-button functions switching, dimming, controlling blinds, value transmitter, calling up light scenes etc.
- One or two functions per button
- To be completed with cover kit
- Inscription field can be illuminated
- One status LED per button, red, green or blue, adjustable
- One operation LED as orientation light and to indicate the programming status red, green or blue adjustable
- Brightness of status LED, operation LED and inscription field adjustable, can be changed during operation, e.g. during night times
- Measurement of room temperature
- Extension unit for room temperature controller
- Disabling function: Disabling or change function mode of single or all button functions
- Alarm function, optional acknowledge by pressing any button
- Energy saving mode
- Integrated bus coupling unit
- Connection for a push-button extension module, 1-4 gang
- Including transparent cover kit for operation on construction site without design covers
- KNX Data Secure compatible with ETS 5.7.7 or ETS 6.1.0 or higher

Spare part:

transparent cover ref.-no.: LS 50 NA

Accessories:

Neutral cover ref.-no.: LS 50 NA W, LS 50 NA WW, LS 50 NA LG, LS 50 NA SW, AL 50 NA-L, ES 50 NA-L, AL 50 NA AN-L, ME 50 NA C-L, ME 50 NA AT-L, ME 50 NA C-L