


Product data sheet

Universal push-button module 3-gang



Reference number

LS 4293 1ST

KNX universal push-button module 3-gang

for cover kit 3-gang, ref.-no.: .. 403 TSA .. in the LS range
 for cover 2-gang with symbols, ref.-no.: .. 402 TSAP .. in the LS range
 for cover 4-gang with symbols, ref.-no.: .. 404 TSAP .. in the LS range
 can be extended by means of a push-button extension module, ref.-no.: 409.. TSEM
 ETS product family: Push-button
 Product type: 3-gang push-button

Intended use

- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush box with dimensions according to DIN 49073

Product characteristics

- KNX medium: TP 256
- Push-button functions switching, dimming, controlling blinds, value transmitter, calling up light scenes etc.
- Measurement of room temperature
- Temperature measurement optionally with internal device sensor and external sensor connected via communication object
- To be completed with cover kit
- Two red status LEDs per button
- One blue operation LED as orientation light and to indicate the programming status
- LED functions alarm message and reducing brightness can be adjusted separately
- Integrated bus coupling unit
- One, two or three functions per button
- Push-button function or rocker function, vertical or horizontal
- Disabling function: Disabling or change function mode of single or all button functions
- Connection for a push-button extension module, 1-4 gang
- KNX Data Secure compatible with ETS 5.7.7 or ETS 6.1.0 or higher
- Can be updated with the ETS Service App